

Scope Specs Table

For: 6-24x | 5-30x | 4-20x | 6-20x

Bottom Magni. = 6x or lower

Top Magni. = 20x or higher

with 10y-Side Parallax

Exposed Turrets

Holdoff Reticle

\$200-500(-2000)

December 5, 2024 | Matthias aka JungleShooter | Airgunner@zohomail.com

Requirements for this Table (a few exceptions are included)

Bottom magnification = 6x or lower

Top magnification = 20x or higher (including a few 40x and 50x)

Minimum parallax = 10 yards or less (a few exceptions with 15y)

Side parallax adjustment

Turrets = exposed (with a few exceptions with capped turrets)

Reticle = holdoff reticle (evenly spaced hash lines or dots for aiming with holdoff/ holdover)

Price = mostly between \$200 and \$500, but some are quite a bit more expensive, and they are included because they have all around very good specs (e.g., large magnification at the top end, or large magnification range; large FoV at the bottom end; high quality glass; etc.)

Abbreviations in the Table

Green is a good thing... – e.g.: a very good warranty, a shorter size or lighter weight than average for this magnification range, a larger than average elevation adjustment range, a very wide field of view (FoV), or some additional feature (bubble level, a 0-stop, turret turn counter, numbers on the hash lines of the reticle), etc.

Red is less of a good thing... – e.g.: a not so great warranty, a longer size or heavier weight than average, a smaller than average elevation adjustment range, a very narrow field of view (FoV), or some other negative or limiting feature, like: a small exit pupil (reducing the eye box), a min. parallax longer than 10y, a reticle without illumination, capped turrets, an FFP reticle without thick outside posts, or a price higher than the max. price that was set for this scope table), etc.

Purple is something noteworthy that could be either good or bad, depending on the shooting scenario... – e.g.: an objective lens that is exceptionally small or large for its magnification (e.g., a small lens allows less light to enter, and reduces the need to focus to correct parallax errors), or an exceptionally short or long eye relief (affecting the scope mounting location and eye/head placement), etc.

Orange is a caution flag, a marginal feature or characteristic... – e.g.: warranty limitations, a marginal FoV, a smaller objective diameter for (supposedly) less light than average for the magnification range, an uneven number of mils or moas per turret turn (not multiples of 5mil or 10moa), a 0-stop that is limited to a certain max. amount of moa (especially for high magnification scopes 24x and up, this is not a “true 0-stop”), a price so low as to shed doubt on the quality of the scope, etc.

SFP vs. **FFP** = table starts with **SFP** (*second focal plane*) scopes, then *first focal plane* (**FFP**)

Thick O/S Posts [for **FFP**] = thick black outside posts, i.e., 3 or 4 of the crosshairs are thick toward the outside (the posts are not hollow rectangles, but filled in with black), which allows seeing the crosshairs easily even when at low magnification. Some have no thick posts, and some have *semi thick* posts.

10x [or 16x, or another number] [for **SFP**] = the magnification at which the holdoff hash lines or dots have been calibrated, i.e., where 1 moa indicated on the reticle actually is 1.047" in reality at 100 yards

Series and Part No. = the manufacturer’s product or parts number; helpful to identify the scope at a seller’s page as some scopes are very similar and the seller’s description is either misleading or insufficient to identify the scope with certainty; also for shopping for the lowest price it helps to enter the number in the search

Discont. = product has been discontinued (but still could be purchased used)

Warranty Info: **Life** = life time warranty | **5y** = 5 years warranty | **OOwn** = warranty only for the original owner | **Unlmt** = unlimited warranty | **Anyb.** = warranty applies to any owner, anybody (e.g., even if you bought it used) | **NoRec.** = no receipt (proof of purchase) required | **Rec.** [or: **R.**] = receipt (proof of purchase) required | **30d** = must register the scope within 30 days of purchase

FoV = Field of View (in ft at 100y):

● *FoV @ bottom magnification:*

A large FoV at the bottom end of the magnification range is important for *hurried close range shooting*, as the large FoV helps rapid target acquisition. Note that a wide FoV is not critical for *unhurried shooting*, i.e., shooting on stationary targets (or quarry that isn’t skittish and gives the shooter time to set up the shot).

The color coding in the table is based on my very personal, unabashedly subjective estimation: *For my kind of hurried close range shooting* I’d like to have a FoV of at least around 3ft at 10y (1m at 10m) (which translates to around 30ft @100y, as FoV is usually reported at 100y; it is color coded black).

The color coding at the bottom end of the magnification is applied irrespective of the scope’s magnification, so naturally 6-24x scopes for example don’t usually get a green rating, but orange or red. Note however that there are sometimes huge differences in FoV between scopes with the same magnification range which makes the bottom end magnification an unreliable indicator of FoV when scope shopping.

41ft or more		40-35ft		34-28ft		27-22ft		21-17ft		16ft or less
7.8° or more		7.7-6.7°		6.6-5.3°		5.2-4.1°		4.0-3.2°		3.1° or less

● *FoV @ top magnification:*

Between two scopes with the same top end magnification the one with a larger FoV is preferable, all other things being equal. This is because the larger FoV might allow to see more clues to how the wind is behaving, or allows to see additional quarry, or makes following the quarry easier if it decides to move. The color coding in the table is based on what is typical for this magnification, i.e., what I have observed to be average for this top magnification.

Examples: At 16x a FoV of 6.3ft normal, whereas a FoV of **4.7ft** is rather narrow and limited. A FoV of **8.5ft** would be great.

Color Coding for the Evaluation of FoV at the <i>Top End</i> Magnification																																				
Magnification	1									7		8	9	10	11	12	13	14	15	16	18	20	22	24	26	28	30	32								
Magnification	1											8								16								32								64
“times life size”	1x									7x		8x	9x	10	11	12	13	14	15	16	18	20	22	24	26	28	30	32		39	46	53	60	64		
Evaluation of Field of View (FoV): Top End* FoV @ 100y																																				
FoV in ft	from worst to best											ft				ft				ft				ft				ft								
red bold	red/orange gets this evaluation if the value is as indicated or worse											8.5	8	7.5		6		5	4.6	4.2	4.0	3.9		3.7			2.8	2.8								
red												9.5	9	8.5		7		5.8	5.2	4.7	4.5	4.4		4.1			3.2	3.2								
orange												10.5	10	9.5		8		6.5	5.9	5.4	5.2	4.9		4.5			3.6	3.6								
Typical Value			color black								13	12	11		9		8	7.1	6.3	5.9	5.5		4.9			4	4									
green	green gets this evaluation if the value is as indicated or better											15	14	13	12	11	10	9	8.1	7.2	6.7	6.2		5.3			4.1	4.1								
green bold												17.5	17	15.5		13		10.1	9.3	8.5	7.7	7		5.7			4.4	4.4								
Magnification	1									7		8	9	10	11	12	13	14	15	16	18	20	22	24	26	28	30	32								

IR = illuminated reticle [Y = yes | **NO**]

Reticle; Ret *D* = "dots" = *enough* dots or hash lines on the crosshairs for holdoffs for elevation and windage

N = "numbers" = the dots or hash lines are numbered for quicker holdoffs

Grid = the reticle is a grid style ("Christmas tree style"): for some shooters and for scope cams it "clutters" the reticle, but it allows for more precise elevation *and* windage holdoffs simultaneously

CD = "center dot" = the crosshairs use a *dot* at the center where the two crosshairs intersect

BDC = bullet drop compensating reticle, meaning that the spacing between the hash lines is uneven and therefore not usable for holdoffs unless shooting the ammo the reticle was calibrated for

Line thickness = Given in both mil and moa for easy comparison. For SFP scopes the line thickness given is only true in relation to the scope image *at the magnification that the reticle has been calibrated*. However, the thickness does not actually change when changing the magnification, only the scope image. For FFP scopes that line thickness in relation to the scope image is always the same, no matter which magnification.

Capped Turrets! BUT Clickable = means that though the turrets are capped, when uncapped they are finger adjustable, the numbers are visible from behind the rifle, and the zero can be reset

Hawke scopes: Careful when purchasing them, new or used. Hawke has the annoying habit of coming out with new scope models but fails to either add the designation "Gen. 2" or to give them a new series name. In addition they have the habit of adding a couple of innocuous letters or numbers to the name of the scope – which mean massive changes in the features or the performance. These letters or numbers are easy to miss for both the

buyers and commercial and private sellers. To assure you are getting the scope with the features you are thinking you are getting, check that the manufacturer's model number is the correct one. The Scope Specs Table notes the numbers for most scope models for that very reason.

Prices

In US dollars

Price Low = lowest *street prices* in US dollars I found in 2019 – and updated according to the list below. An additional extra low *street* price is separated by a *comma* ,

Price Mfctr.'s = manufacturer's price [it's the last price in that field, after the semicolon ;]

Prices and/or models updated as follows: 2021-06: Hawke | 2021-07: Shepherd | 2022-02:

Alpen | Arken | Riton | Bushnell | 2023-05: Falcon | 2023-06: Trijicon | 2023-07:

Discoveryopt, aka Discovery | Primary Arms | 2024-06: Vector (most)

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024	Price: Low; Mfctr.'s in US \$	Warranty	Springer-Rated	Magnification	FoV = Field of View @ 100y (ft)	Obj. Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adj. (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick O/S Posts? FFP – SFP Calibration at ?	Enough Dots, No's, Grid CenterDot	Line thickness	Tube Diameter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Brand: Series	Part No.																			
SFP Scopes																				
UTG: Accushot No. SCP3-UG6245A0IEW	209; 310	Life		6-24x	15-5	56	8-2.2	Y	??	1/8 moa	15 moa	MOA ≠	≠MIL	SFP 10x	D*		30	32.2 910g	17.5" 44c	*Should state glass etched reticle
Nikko: Diamond Long Range No. NDSI62450LRHMD •Ret. HMD	250; ?	Life, 0.Own		6-24x	21-5	50		Y	40	1/4 moa		MOA ≠	≠MIL	SFP x?	D		30	27.8 788g	15.4" 39c	
Vector: Atlas No. SCOL-04	399; ?	5y, Rec.		5-30x	24.6-3.8	56	11-1.9	Y	80	1/8 moa	15 moa	MOA ≠	≠MIL	SFP x?	D, N	?	35	35.3 1000g	14.8" 38c	
MTC: Viper Pro Tactical	520; ?	Life ^{300R} , 0.Own		5-30x	24-4 ²	50		Y	42	1/4 moa	10 moa	MOA ≠	≠MIL	SFP x?	D	?	30	25.8 732g	16.4" 42c	not customizable
MTC: Viper Pro	570; ?	Life ^{300R} , 0.Own		5-30x	24-4 ²	50		Y	42	1/4 moa	30 moa	MOA ≠	≠MIL	SFP x?	D	?	30	30.7 869g	16.4" 42c	Customizbl. Turrets Magnifier Cap
Bushnell: Engage No. REN62450DG	450; 350, 540	Life, NoRec.		6-24x	18-4	50	?	NO	50	1/8 moa	8 moa	MIL ≠	≠MOA	SFP x?	D	.05 ^{mi} .18 ^{mo}	30	23.7 672g	14.2" 36c	
Vector: Aston No. SCOL-24	?; 430	5y		5-30x	19.9-3 ³	56	11-1.9	Y	50	1/4 moa	15 moa	MOA =	=MOA	SFP 10x	D, CD		30	29.5 835g	15.7" 40c	Parallax 20y! ! Locking Turrets
Hawke: Sidewinder 30 SF No. 17220 Discontinued	439; 600	Life, R. 0.Own	Yes!	6-24x	15-4	56	9-2.0	Y	62	1/4 moa	15 moa	MOA ≠	≠MIL	SFP 20x	D	?	30	29.8 844g	15.9" 40c	
Aztec: Emerald SFP	440; –	Life		5.5-25x	19 ¹ -4 ²	50	?	NO	c. 40?	1/4 moa	15 moa	MOA =	=MOA	SFP 18x✓	D, N	?	30	25.4 720g	14.4 37c	
Optisan: EVX Gen. 2: 5-20x50i No. 37526	430; 440	Life		5-20x	23-6	50	10-2.5	Y	50	0.1 mil	4.8 mil	MIL =	=MIL	SFP x?	D, (N)	.05 ^{mi} .18 ^{mo}	30	27.0 765g	14.4" 37c	
Sightron: S-TAC: [SFP] •Ret. MOA-2 No. S-TAC4-20X50MOA	470; 540	Life		4-20x	23.6-4.4	50	?	NO	80 ^{40 wind-age}	1/4 moa	15 moa	MOA =	=MOA	SFP 20x	D	.03 ^{mi} .10 ^{mo}	30	23.8 675g	14.8" 38c	Dialing Turrets (capped w/ N1) Turn Counter
Hawke: Sidewinder 30 SF No. 17150	479; 639	Life, R. 0.Own	Yes	6.5-20x	19.5-6 ³	44	7-2.2	Y	95	0.1 mil	6 mil	MIL =	=MIL	SFP 20x	D, Grid	?	30	24.0 680g	13.3" 34c	T Turn Counter
Vector: Paragon 30mm Gen. 2 No. SCOL-27	449; 449	Life, NoRec.		6-30x	18.8-3.8	56	9.1-1.5	Y	60	0.1 mil	8 mil	MIL =	=MIL	SFP 10x	D, N, Grid		30	24.7 700g	14.4" 37c	Parallax 15y Locking Turrets
Vector: Paragon 30mm Gen. 2 No. SCOL-26	420; 529	Life, NoRec.		5-25x	22.5-4.5	56	8-2.2	Y	60	0.1 mil	8 mil	MIL =	=MIL	SFP x?	D, N, Grid		30	23.6 670g	14.4" 37c	Parallax 15y Locking Turrets
Vector: Tarus HD HT No. SCOL-46	400!; 299	Life		6-24x	17.9-4.5	50	8.3-2.2	Y	60	0.1 mil	6 mil	MIL =	=MIL	SFP 10x	D, N, CD		30	26.9 763g	14.3" 36c	0-Stop; Turn Counter; Large Turrets

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024 Brand: Series Part No.	Price: Low; Mfgtr.'s in US \$	War-ranty	Sprin-ger-Rated	Magni-fication	FoV =Field of View @ 100y (ft)	Obj. ∅ Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adjnt (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick O/S Posts? FFP — SFP Calibration at ?	Enough Dots, No's, Grid CenterDot?	Line thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Vector: Taurus 34mm HD •MIL Ret. SCFF-46 •MOA Ret. SCFF-51	Not avail-able yet	Life		6-24x	20.9-5.2	50	?	Y	80 36 wind-age	0.1 mi ¼ mo	10 mi 25 mo	MIL = MOA =	=MIL =MOA	SFP 20??x	D?, N?, Grid?, CD?	?	34	32.7 926g	13.9" 35c	0-Stop?; Turn Counter?
Element: Helix SFP •MIL Ret. PR-1C SFP •MOA Ret. EHR-1C SFP	400; —	Life, NoRec.		6-24x	19 ¹ -4 ²	50	9-2.0	NO	65	0.1 mi ¼ mo	6 mil 15 mo	MIL = MOA =	=MIL =MOA	SFP 24x	D, N	?	30	26.0 737g	13.3" 36c	Toolless Re-zero; 0-Stop; Turn Counter
Hawke: Airmax 30 SF No. 13320 Discontinued	408; 480	Life, R. O.Own	Yes!	6-24x	17 ³ -4.5	50	8-2.0	Y	65	¼ moa	15 moa	MOA ≠	≠MIL	SFP 10x	D	?	30	26.7 757g	15.6" 40c	"small Eyebow" Locking Turrets
Hawke: Airmax 30 SF Compact No. 13220	395; 459	Life, R. O.Own	Yes!	6-24x	21.9-5.5	50	8-2.1	Y	53	0.1 mil	6 mil	MIL =	=MIL	SFP 10x	D	?	30	23.6 670g	13.0" 33c	Capped Turrets BUT Large for Clicking! T Turn Counter
Vector: Paragon 1 inch Zero Stop No. SCOL-T44 (not SCOL-44)	374; 499	Life		4-20x	27.9-5.6	50	10-2.5	Y	60	0.1 mil	10 mil	MIL =	=MIL	SFP 20x	D, mini-Grid, CD	.04 ^{mi} .15 ^{mo}	1"	27.0 765g	13.5" 34c	Locking Turrets; 0-Stop; Large Turrets
Hawke: Frontier SF •Mil Pro Ret. No. 18130	479; 629	Life, R. O.Own	Yes	4-20x	28-6	44	11-2.2	Y	63	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid	?	1"	20.6 584g	13.2" 34c	3 Screws to rezero; Locking Turrets; 0-Stop
Hawke: Frontier SF •Ret. Mil Pro No. 18140	529; 699	Life, R. O.Own	Yes!	5-25x	22.5-4.5	50	10-2.0	Y	37	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid	?	1"	22.2 628g	14.4 36c	3 Screws to rezero; Locking Turrets; 0-Stop
Hawke: Sidewinder 30 SF •20x Half Mil Ret. No. 47260	499; 659	Life, R. O.Own	Yes	6-24x	21 ³ -5.4	56	9-2.3	Y	70	0.1 mil	6 mil	MIL =	=MIL	SFP 20x	D, Grid	?	30	27.3 775g	14.3" 36c	T Turn Counter
Vector: Continental X6 30mm • Tactical Lock No. SCOL-33T • Tactical ARI No. SCOL-54 • Tactical No. SCOL-43	?; 529	Life, NoRec.		4-24x	31 ¹ -5 ²	50	9-2.1	Y	67	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid, CD		30	23.6 670g	14.6" 37c	Parallax 15y; 3 Screws to rezero •Locking Turrets •0-Stop; Large Turrets •0-Stop; Large Turrets; Color FDE
Vector: Continental X8 ED Tactical No. SCOL-T51	?; 765	Life, NoRec.		4-32x	30.7-3.8	56	8-1.7	Y	70	0.1 mil	8 mil	MIL =	=MIL	SFP ?x	D, N, Grid		30	28.0 795g	15.1" 39c	Parallax 17-15y (yes); 0-Stop; Locking Turrets
Hawke: Frontier SF •Mil Pro Ret. No. 18130	479; 629	Life, R. O.Own	Yes	4-20x	28 ² -5.7	44	11-2.2	Y	63	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid	?	1"	20.6 584g	13.2" 34c	3 Screws to rezero; Locking Turrets; 0-Stop
Hawke: Frontier 30 SF •Mil Pro Ret. No. 18441	740; 949	Life, R. O.Own	Yes	5-30x	22.5-3.6	56	11-1.9	Y	57	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid	?	30	25.5 724g	15.8" 40c	Parallax 15y 3 screws to rezero; Locking Turrets; 0-Stop
Hawke: Frontier 30 SF •Mil Pro Ret. No. 18431	699; 899	Life, R. O.Own	Yes	4-24x	28 ² -4.8	50	12-2.1	Y	73	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid	?	30	23.4 662g	14.5" 37c	Parallax 15y; 3 screws to rezero; Locking Turrets; 0-Stop
Vector: Continental X6 Tactical SFP • Tactical Lock No. SCOL-22T • Zero Stop Tactical No. SCOL-47	590; 599	Life		5-30x	24.9-4 ²	56	9.5-1.9	Y	57	0.1 mil	8 mil	MIL =	=MIL	SFP 20x	D, N, Grid, CD	.03 ^{mi} .10 ^{mo}	30	25.6 725g	15.7" 40c	Parallax 15y — or 10y?; 3 screws to rezero; •Locking Turrets •0-Stop; Large Turrets
Maven: RS.5 Only SHR-MIL Ret.!	1400; 1400	Life	?	4-24x	27.8-4.6	50	8 ⁵ -2.1	Y	100	0.1 mil	10 mil	MIL =	=MIL	SFP 24x	•5mi Elev., CD	?	30	25.5 723g	14.4" 37c	0-Stop; Windage capped

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024 Brand: Series Part No.	Price: Low; Mfctr.'s in US \$	War-ranty	Springer-Rated	Magni-fication	FoV = Field of View @ 100y (ft)	Obj. Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adj. (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick O/S Posts? FFP – SFP Calibration at ?	Enough Dots, No's, Grid CenterDot	Line thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Vector: Taurus 34mm ED No. SCOL-55	?; 509	Life		3-24x	41-5 ¹	56	19-2.3	Y	100	0.1 mil	10 mil	MIL =	=MIL	SFP 20x	D, N, Grid, CD	.03 ^{mi} .10 ^{mo}	34	34.9 991g	13.5" 35c	Parallax 10y✓ 0-Stop; Turn Counter
Trijicon: Tenmile •Red Dot No. 1M42450-C-3000007 •Green Dot No. 1M42450-C-3000008	900, 1200; 1890	Life	?	4-24x	28.5-4.7	50	8-2.0	Y	100 70 Wind-age	0.1 mil	8 mil	MIL =	=MIL	SFP 24x	D	.06 ^{mi} .20 ^{mo}	30	25.7 729g	14.5" 37c	0-Stop; Turn Counter; Capped Windage Turret
Falcon (UK): T50i Designed for FT Range Finding to 55y	500; –	Life ✓	?	5-50 x	24.8-2.5	60	?	Y 30 Wind-age	70	1/8 moa	10 moa	MOA =	=MOA	SFP 25x	D, N, CD	.02 ^{mi} .08 ^{mo}	34	32.8 930g	16.1" 41c	Locking Turrets; No Turn Counter with 10moa/turn
Sightron: S6 [= SVI] SFP •MOA-7 No. 66002	1500; 1600	Life	?	5-30x	22.7-3.8	56	?	Y 60 Wind-age	80	1/4 moa	20 moa	MOA =	=MOA	SFP 30x	D, N, CD	.03 ^{mi} .10 ^{mo}	34	33.3 944g	16.7" 42c	0-Stop; 3 screws to rezero
Delta: Stryker HD •DLS-1 Ret. [MIL] Ret. No. DU-2504 •DLS-3 MOA Ret. No. DU-2506	1590; –	10y, Rec.	?	5-50 x	19.2-2 ¹	56	7-1.1	Y 50 Wind-age	100	0.05 mil 1/8 moa	10 mi 25 mo	MIL =	=MIL	SFP 40x	•D, CD •D, N, CD	.005 ^{mi} .02 ^{mo}	34	38.8 1100g	14.3" 36c	0-Stop; Turn Counter
Trijicon: Tenmile •MRAD Center Dot w/ Wind Holds No. 1M5056-C-3000017 •MOA Long Range No. 1M5056-C-3000016	1816; 2837	Life	?	5-50 x	21 ⁻² -2 ¹	56	7-1.0	Y 50 Wind-age	100	0.05 mil 1/8 moa	4 mi ? mo	MIL =	=MIL	SFP 40x	D, N, mini Grid, CD	.01 ^{mi} .03 ^{mo}	34	38.4 1089g	16.0" 41c	0-Stop; Turn Counter; Capped Windage Turret
FFP Scopes																				
FFP Scopes – without Thick Outside Posts in the Reticle																				
Monstrum: •G1 Ret. No. FFPS62450-R •G2 Ret. No. G2-BFFPS62450-R	•230 •200	1y		6-24x	???	50	?	Y ? 80	?	1/4 moa	15 moa	MOA =	=MOA	FFP No Thick Posts	D	?	30	30.0 29.0	16.6" 15.5"	
Sun Optics: FFP Variable No. CS41-62450	400; 557	1y		6-24x	17-4	50	8-2.0	NO ??	??	0.1 mil	6 mil	MIL =	=MIL	FFP ⁵⁴ No Thick Posts	D	.10 ^{mi} .34 ^{mo}	30	26.0 737g	14.5" 37c	Reticle must be very thick! ⁵⁴
Vector: Veyron 6-24x44 No. SCFF-23	198; 289	5y	Yes	6-24x	17.5-4 ³	44	7-1.8	NO 50	50	0.1 mil	6 mil	MIL =	=MIL	FFP ³ No Thick Posts	D	.025 ^{mi} .08 ^{mo}	30	20.5 580g	11.7" 30c	Locking Turrets
Vector: Marksman 6-24x50 No. SCFF-26 (not the 6-25x50, SCFF-11)	?; 230	5y, Rec.		6-24x	17-5	50	8-2.1	NO 60	60	0.1 mil	6 mil	MIL =	=MIL	FFP ¹⁶ No Thick Posts	D, N, Grid	?	30	24.7 700g	14.2" 36c	Locking turrets
MTC: King Cobra F1 446, 629, 300 – 0.Own	446, 629, 300 – 0.Own	Life, R. 0.Own		6-24x	16-4	50	?	Y 38 (??)	38	0.1 mil	5 mil	MIL =	=MIL	FFP ¹⁸ No Thick Posts	D		30	26.3 746g	14.4" 37c	Locking Turrets Magnify. Lens Cap
Hawke: Sidewinder 30 SFFFP No. 17420 Discontinued	500; 600	Life, R. 0.Own	Yes!	6-24x	17-4	56	9-2.0	Y 60	60	0.1 mil	5 mil	MIL =	=MIL	FFP ¹⁰ No Thick Posts	D	?	30	31.1 880g	15.9" 40c	
Hawke: Airmax 30 FFP SF No. 13352	496; 589	Life, R. 0.Own	Yes!	6-24x	21 ⁰ -5 ²	50	8-2.1	Y 57	57	0.1 mil	6 mil	MIL =	=MIL	FFP No Thick Posts	D	?	30	27.0 765g	14.9" 38c	Capped Turrets! BUT Clickable
Hawke: Vantage 30 WA FFP No. 14304	424; 589	Life, R. 0.Own	<12 FPE	6-24x	21 ⁰ -5 ²	50	8-2.1	Y 60	60	0.1il	6 mil	MIL =	=MIL	FFP No Thick Posts	D	?	30	26.6 755g	14.9" 38c	
Vector: Taurus No. SCFF-14	?; 449	Life, NoRec.		5-30x	20.4-3.5	56	11-1.8	Y 40	40	0.1 mil	6 mil	MIL =	=MIL	FFP ² No Thick Posts	D, N	?	30	28.7 813g	15.6" 40c	Parallax 17y (20y stated)
Konus (Italy): Pro F30 No. 7297	590; ?	Life		6-24x	16-4	52	8-2.2	Y 60	60	0.1 mil	5 mil	MIL =	=MIL	FFP ¹² No Thick Posts	D	.04 ^{mi} OR? .05 .14 ^{mo}	30	28.6 810g	16.4" 42c	Cant Bubble Large Parallax T.
Hawke: Sidewinder 30 FFP •FFP Half Mil Ret. No. 17460 •FFP MOA Ret. No. 17461	629, 799; 670, 799	Life, R. 0.Own	Yes	6-24x	21 ⁻³ -5.4	56	9-2.3	Y 70	70	0.1mi 1/4mo	6 mil 15 mo	MIL =	= MIL	FFP No Thick Posts	D, Grid	?	30	27.3 775g	14.3" 36c	T Turn Counter

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024 Brand: Series Part No.	Price: Low; Mfctr.'s in US \$	War-ranty	Springer-Rated	Magni-fication	FoV = Field of View @ 100y (ft)	Obj. Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adj. (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	FFP Thick O/S Posts? – SFP Calibration at ?	Enough Dots, No's, CD Grid CenterDot	Line thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Vector: Taurus No. SCFF-17	380; 430	Life, NoRec.		4-24x	25.5-4.2	50	12-2.1	Y	50	0.1 mil	6 mil	MIL =	=MIL	FFP ²³ No Thick Posts	D, N, CD	.04 ^{mi} .14 ^{mo}	30	27.1 770g	15.0" 38c	Parallax is 10y. Locking turrets
Hawke: Frontier 30 FFP •MilPro 20xRet. No. 18530	950; 1050	Life, R. 0.Own	Yes	4-20x	28 ⁻² -5.7	50	12-2.5	Y	80	0.1 mil	8 mil	MIL =	=MIL	FFP ³⁶ No Thick Posts	D, N, Grid	?	30	22.2 630g	13.2" 34c	Parallax 15y 3 Screws to rezero; Locking Turrets; 0-Stop
Hawke: Frontier 30 FFP •MilPro 25xRet. No. 18540	849; 1049	Life, R. 0.Own	Yes	5-25x	22.5-4.5	56	11-2.2	Y	65	0.1 mil	8 mil	MIL =	=MIL	FFP ¹⁴ No Thick Posts	D, N, Grid	?	30	24.6 698g	14.4" 37c	Parallax 15y 3 Screws to rezero; Locking Turrets; 0-Stop
FFP Scopes – with Thick Outside Posts in the Reticle																				
Vector: Tourex No. SCFF-19	?; 280	5y, Rec.		6-24x	18-5	50	8-2.1	Y	50	¼ moa	15 moa	MOA =	=MOA	FFP ¹⁷ Thick O/S Posts	D, N but 4, 12, 20, 28, 36	?	30	26.3 745g	14.3" 37c	0-Stop
Monstrum: •G3 Ret. No. G3F62450 •GH Ret. No. FFP62450-H	•250 •200	1y		6-24x	18-5	50	?	Y	80	¼ moa	15 moa	MOA =	=MOA	FFP Thick O/S Posts	D	?	30	30.0 850g	15.8" 16.6"	Parallax is 10y
Aztec: Emerald FFP	540; –	Life	Yes!	5.5-25x	19 ⁻¹ -4 ⁻²	50	?	Y	c. 40?	¼ moa	15 moa	MOA =	=MOA	FFP ¹⁹ Thick O/S Posts	D, N mini Grid	?	30	25.4 720g	14.4 37c	"Low DoF"
ACME Machine •TR-MIL Ret. No. 08-625 •TR-MOA Ret. No. 08-624	?; 300			6-24x	17-4	50	8-2.1	Y	60	0.1mi ¼mo	??mi 12 mo	MIL = MOA =	=MIL =MOA	FFP ²⁰ Thick O/S Posts	D		30	28.5 808g		Parallax is 10y. T. Turn Counter
Sightron: S-TAC: [FFP] •Ret.MIL No. S-TAC4-20X50FFP2SIRMH	660; 800	Life		4-20x	22-4	50	?	Y	80 40 wind-age	0.1 mil	5 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N	.035 ^{mi} .12 ^{mo}	30	25.6 725g	15.0" 38c	0-Stop. T Turn Counter
Element: Nexus •APR-1C MRAD Ret. •APR-2D MRAD Ret. •EHR-1C MOA Ret. •EHR-1D MOA Ret.	1500; 1500	Life		5-20x	23 ⁻³ -5.8	50	8-2.5	Y	80 50 wind-age	0.1mi ¼mo	10 mi 20 mo	MIL = MOA =	=MIL =MOA	FFP Thick O/S Posts	•D, N •+Grid •D, N •+Grid	?	30	28.0 794g	13.8" 35c	0-Stop. T Turn Counter. Toolless Rezero
Hi-Lux (US): PentaLux TAC-VF 4-20x50 FFP G2	539; 575	Life, Rec.	No	4-20x	28-6	50	12-2.5	Y	80	0.1 mil	12 mil	MIL =	=MIL	FFP ³² Thick O/S Posts	D, N	?	30	27.9 791g	14.7" 37c	Locking Turrets Throw Lever
Swampfox (US): Warhawk •Sharpsh. Grid Ret. MIL No. TWK42050-3L •Sharpsh. Grid Ret. MOA No. TWK42050-3M	??; 659	Life (50000 rounds)		4-20x	32 ⁰⁻ -7 ⁻²	50	13-2.4	Y	90	0.1mi ¼mo	10 mi 25 mo	MIL = MOA =	=MIL =MOA	FFP ³⁴ Semi Thick Posts	D, N, Grid	?	34	32.8 930g	15.0 38c	Locking Turrets
Athlon: Helos BTR Gen. 2 •APRS6 MIL Ret. No. 214109 •APLR6 MOA Ret. No. 214108	500; 712	Life, NoRec.		4-20x	28-6	50	?	Y	100	0.1mi ¼mo	10 mi 25 mo	MIL = MOA =	=MIL =MOA	FFP Thick O/S Posts	D, N, Grid	.05 ^{mi} .17 ^{mo} .05 ^{mi} .17 ^{mo}	30	27.6 782g	13.3" 34c	0-Stop T Turn Counter
Nikko: Diamond FFP 30 •PRR Ret. No. NSFFP62450PRR •Skeleton HMD Reticle No. NSFFP62450HMD	300; ?	Life, 0.Own		6-24x	19-5	50	?	Y	50	0.1 mil	6 mil	MIL =	=MIL	FFP ²⁷ O/S Posts •Thick •Not Thick	D, N D, –	.05 ^{mi} .17 ^{mo}	30	24.0 680g	14.2" 36c	Locking Turrets
Nikko: Diamond FFP 34 •PRR Ret. No. NSFFP3441644PRR •Skeleton HMD Ret. No. NSFFP3462450PRR	430; ?	Life, 0.Own		6-24x	21-5	50	?	Y	80	0.1 mil	6 mil	MIL =	=MIL	FFP ²⁸ O/S Posts •Thick •Not Thick	D, N D, –	.05 ^{mi} .17 ^{mo}	34	26.5 750g	14.2" 36c	Locking Turrets
Optisan: EVX, Gen. 2: 6-24x50 F1 •w/ IR No. 37583 •w/o IR No. 37534	?; 560	Life		6-24x	19.4-4.9	50	8-2.1	Ei th er	50	0.1 mil	4.8 mil	MIL =	=MIL	FFP ²¹ Semi Thick Posts	D, (N)	?	30	26.5 751g	14.8" 38c	Locking Turrets
Riton (US): 3 Conquer	500; 587	Life, NoRec	Yes	6-24x	17-4	50	8-2.1	Y	70	0.1 mil	6 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid	.045 ^{mi} .15 ^{mo}	30	27.1 768g	14.1" 36c	0-Stop

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024 Brand: Series Part No.	Price: Low; Mfctr.'s in US \$	War-ranty	Springer-Rated	Magni-fication	FoV = Field of View @ 100y (ft)	Obj. Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adj. (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick FFP O/S Posts? Calibration at ?	Enough Dots, No's, CD CenterDot	Line thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Swampfox (US): Patriot •Sharpsh. Grid Ret. MIL No. PAT82450-L •Sharpsh. Grid Ret. MOA No. PAT82450-M	300; 429	Life (50000 rounds)		6-24x	17.5-4 ²	50	8-2.1	NO	65	0.1mi	6 mi	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid	?	30	24.0 680g	14.5 37c	
Blackhound (US): Genesis 6-24x50 FFP •MIL •MOA	?; 400	Life, Anyb.	?	6-24x	16-4	50	?	Y	70	0.1mi	5 mi	MIL =	=MIL	FFP ⁹ Thick O/S Posts	D, N	?	30	27.5 780g	14.1" 36c	0-Stop T Turn Counter
Athlon: Argos BTR Gen 1 •MIL Ret. No. 214061 Discontinued •MOA Ret. No. 214060	297; 445	Life, NoRec.		6-24x	17-4	50	8-2.1	Y	60 (a user reported 70)	0.1mi	5 mil	MIL =	=MIL	FFP ¹³ Thick O/S Posts	D, N, Grid	.02 ^{mi} .07 ^{mo} .04 ^{mi} .14 ^{mo}	30	29.6 835g	14.1" 36c	T Turn Counter "Tracks, Wide DoF, small Eye Box"
Athlon: Argos BTR Gen 2 •MIL Ret. No. 214063 •MOA Ret. No. 214062	380; 450	Life, NoRec.		6-24x	16.7-4.5	50	8-2.1	Y	60 (a user reported 70)	0.1mi	6 mi	MIL =	=MIL	FFP ³¹ Thick O/S Posts	D, N, Grid	.02 ^{mi} .07 ^{mo} .04 ^{mi} .14 ^{mo}	30	30.3 859g	14.1" 36c	0-Stop T Turn Counter
Vortex: Diamondback Tactical •MIL Ret. No. DBK-10029 •MOA Ret. No. DBK-10028	400, 300; 500	Life		6-24x	18 ⁰ -4.5	50	8-2.1 calculated	NO	65	0.1mi	6 mi	MIL =	=MIL	FFP ⁸ Thick O/S Posts	D, N, Grid	.03 ^{mi} .12 ^{mo}	30	24.6 697g	14.3" 36c	"Tracks" "small Eyebox"
Element: Helix FFP •MIL Ret. APR-2D MRAD •MOA Ret. APR-2D MOA	480; —	Life, NoRec.		6-24x	18 ⁻³ -4.6	50	9-2.2	NO	65	0.1 mi	6 mi	MIL =	=MIL	FFP ³⁰ Thick O/S Posts	D, N, Grid	?	30	26.0 737g	14.3" 36c	Toolless Re-zero; 0-Stop; Turn Counter
Bushnell: Match Pro •w/ IR No. MP6245BF8 •w/o IR No. MP6245BF2	—; 500, 450	Life NoRec.		6-24x	18-4	50	?	Ei th er	65	0.1 mil	10 mil	MIL =	=MIL	FFP ⁴⁴ Thick O/S Posts	D, N, Grid	.05 ^{mi} .17 ^{mo}	30	29.8 845g	14.0" 36c	Locking Turrets; Toolless Re-zero
Athlon: Helos BTR •MIL Ret. No. 214107 Gen. 1 = Discontinued •MOA Ret. No. 214106	459, 570; 712	Life, NoRec.		6-24x	17-5	50	8-2.1	Y	60	0.1mi	6 mil	MIL =	=MIL	FFP ⁶ Thick O/S Posts	D, N, Grid	.02 ^{mi} .07 ^{mo} .04 ^{mi} .14 ^{mo}	30	29.7 842g	14.0" 36c	T Turn Counter Locking Turrets
Athlon: Midas TAC •MIL APRS2 Ret. No. 213075 •MIL APRS3 Ret. No. 213077 •MOA APLR4 Ret. No. 213076	•630 756 •670 837 •670 837	Life, NoRec.		6-24x	17.8-4.6	50	11-1.8	Y	85 80 Wind-age	0.1mi	10 mi	MIL =	=MIL	FFP ⁵ Thick O/S Posts	D, N D, N, Grid D, N, Grid	.03 ^{mi} .10 ^{mo} .036 ^{mi} .12 ^{mo}	30	26.3 746g	14.6" 37c	0-Stop T Turn Counter Windage Capped
Delta: Stryker HD •DLR-1 Ret. No. DO-2515 •DPRC-1 Ret. No. DO-2514	1595; —	10y Rec.		35-21x	33.3-5.7	44	?	Y	170 80 Wind-age	0.1 mil	10 mil	MIL =	=MIL	FFP Thick O/S Posts	•D, (N), CD •D, N, CD, Grid	.05 ^{mi} .17 ^{mo} .035 ^{mi} .12 ^{mo}	34	28.4 805g	12.4" 32c	0-Stop T Turn Counter Locking Turrets Windage Capped ▲Eye relief from 7.1-9.9cm
Alpen: Apex No. 4015	720; 980	Life, 60d		45-27x	22 ⁻² -3.8	50	10-1.9	Y	80	1/4 moa	25 moa	MOA =	=MOA	FFP Thick O/S Posts	D	?	30	heavy ???	16.9" 43c	
Shepherd (US): BRS •BRS-MIL Ret. •BRS-MOA Ret.	749; 849	Life, 00wn		5-25x	22.5-4.5	56	?	Y	60	0.05 mil	? mil	MIL =	=MIL	FFP ³⁵ Thick O/S Posts	D, N, Grid	? ? .04 ^{mi} .13 ^{mo}	34	37.9 1075g	15.4 39c	T Turn Counter Locking Turrets
Swampfox (US): Warhawk •Sharpsh. Grid Ret. MIL No. TWK52556-3L •Sharpsh. Grid Ret. MOA No. TWK52556-3M	569; 689	Life (50000 rounds)		5-25x	24.4-4.6	56	11-2.2	Y	90	0.1mi	10 mi	MIL =	=MIL	FFP ³⁴ Semi Thick Posts	D, N, Grid	?	34	36.8 1043g	15.4 39c	Parallax 15y Locking Turrets
Swampfox (US): Kentucky Long •Sharpsh. Grid Ret. MIL No. KTK53056-4L •Sharpsh. Grid Ret. MOA No. KTK53056-4M	467; 599	Life (50000 rounds)		5-30x	21.8-3.4	56	9-1.7	Y	80	0.1mi	6 mi	MIL =	=MIL	FFP ²² Semi Thick Posts	D, N, Grid	?	30	31.8 902g	15.5" 39c	Parallax 15y Locking Turrets

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024 Brand: Series Part No.	Price: Low; Mfctr.'s in US \$	War-ranty	Spring-ger-Rated	Magni-fication	FoV =Field of View @ 100y (ft)	Obj. ∅ Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adj. (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	FFP Thick O/S Posts? — SFP Calibration at ?	Enough Dots, No's, CD CenterDot	Line thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Athlon: Helos BTR Gen. 2 •MIL Ret. No. 214114 •MOA Ret. No. 214113	600; 750	Life, NoRec.		6-24x	19.9-5.1	56	?	Y	100	0.1mi	10 mi	MIL =	=MIL	FFP ⁶ Thick O/S Posts	D, N, Grid	.03 ^{mi} .10 ^{mo} .04 ^{mi} .12 ^{mo}	34	34.5 978g	14.3" 37c	0-Stop T Turn Counter
Zero Tech (US): Vengeance	?; 800	Life, NoRec.		5-25x	21 ³ -5.7	56	9-1.9	Y	96 69 Win-dage	0.1 mil	10 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid	.04 ^{5mi} .15 ^{mo}	34	39.0 1105g	15.1" 38c	Parallax 15y 3 screws de rezero; Locking Turrets; 0-Stop
Arken (US): EPL4 •MIL Ret. No. EPL4-6241VHR •MOA Ret. No. EPL4-6240VHR	400; 440	Life		6-24x	18.6-4.7	50	?	Y	68 40 Win-dage	0.1mi	8 mi	MIL =	=MIL	FFP ⁴² Thick O/S Posts	D, N, CD	.03 ^{mi} .10 ^{mo}	30	23.7 672g	13.8" 35c	0-Stop, 3 screws to rezero, T Turn Counter
Swampfox (US): Kentucky Long •Sharpsh. Grid Ret. MIL •Sharpsh. Grid Ret. MOA No. KTK42450-4L No. KTK42450-4M	459; 569	Life (50000 rounds)		4-24x	30.9-4.7	50	11-2.0	Y	90	0.1mi	6 mil	MIL =	=MIL	FFP ³³ Semi Thick Posts	D, N, Grid	?	30	28.2 800g	15.1 38c	Locking Turrets
Falcon (UK): S30 Gen. 1 (–2020) No. S3001 Discontinued	377, 423; –	10y, 0.Own		5-30x	24 ⁰ -3.9	56	11-1.9 canted	NO	57	0.1 mil	10 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N	.04 ^{mi} .14 ^{mo}	30	32.5 920g	15.8" 40c	T Turn Counter
Falcon (UK): S30 Gen. 2 (2020–) Discontinued	?; –	10y, 0.Own		5-30x	24-4	56	11-1.9 canted	NO	90	0.1 mil	12 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid	?	34	36.0 1020g	14.6" 37c	No T Turn Counter, but 12mil/turn
Hi-Lux (US): Phenom 5-30x56 FFP	507; 599	Life, Rec.	No	5-30x	23-4	56	10-1.2	Y	90	0.1 mil	12 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid	.05 ^{mi} .17 ^{mo}	34	32.0 907g	14.7" 37c	Locking Turrets 12mil/turn
Hawke: Frontier 34 FFP •MIL Ret. No. 18640 •MOA Ret. No. 18641	1260; 1400	Life, R. 0.Own	Yes	5-30x	22.5-3.8	56	11-1.9	Y	100 53 Win-dage	0.1mi 1/4mo	8 mil	MIL =	=MIL	FFP Semi Thick Posts	D, N, Grid	.03 ^{mi} .11 ^{mo}	34	29.3 830g	15.4" 39c	Parallax 15y 3 screws; Locking Turrets; Zero Stop
Vortex: Strike Eagle •MIL Ret. No. SE-52504 •MOA Ret. No. SE-52503 Some fails!: https://www.youtube.com/watch?v=u06iY4xpDs	700; 800	Life		5-25x	24 ⁰ -5.2	56	?	Y	110 78 Win-dage	0.1mi 1/4mo	10 mi 25 mo	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid	.03 ^{mi} .11 ^{mo}	34	31.8 902g	15.5" 39c	Parallax 15y 0-Stop with 47moa Limit Locking Turrets
Element: Titan •MIL Ret. APR-2D •MOA Ret. APR-2D •MOA Ret. EHR-1C •MIL Ret. APR-1C	800; –	Life, NoRec.		5-25x	24 ¹ -4.9	56	11-2.1	Y	90 50 Win-dage	0.1mi 1/4mo	10 mi 25 mo	MIL =	=MIL	FFP ²⁹ Thick O/S Posts	D, N, Grid, CD D, (N). D, N, CD.	??	34	39.0 1105g	15.2" 39c	Parallax 15y 0-Stop with 47moa Limit Toolless Re-zero; T Turn Counter
Riton: 5 Conquer (or X5) •PSR MIL Ret. •BAF MOA Ret.	550, 600; 824	Life	Yes	5-25x	22.5-4.5	50	10-2.2	Y	70	0.1mi 1/4mo	10 mi 25 mo	MIL =	=MIL	FFP ³⁹ Thick O/S Posts	D, N, Grid, CD	.035 ^{mi} .12 ^{mo}	34	34.0 963g	15.4" 39c	0-Stop with 70moa Limit ⁴² ; 3 Screws to rezero
Falcon: Endura •MIL B2GD B28 Grid-Dot Ret. No. FO-B252 •MOA M40 Plus-Dot (M4PD) Ret. No. FO-B251	680; –;	Life		35-25x	27 ⁰ -4.4	56		Y	110	0.1mi 1/4mo	10 mi 25 mo	MIL =	=MIL	FFP ⁴⁶ Thick O/S Posts	D, N, Grid	.04 ^{mi} .12 ^{mo}	34	35.1 995g	14.8" 38c	True 0-Stop; T-Counter
Falcon (UK): Endura S40i	600; –	Life		5-40x	23.7-3.3	56	?	Y	100	0.1 mil	10 mil	MIL =	=MIL	FFP ⁶² Thick O/S Posts	D, N, Grid, CD	? ^{mi} ? ^{mo}	34	40.2 1140g	15.7" 40c	True 0-Stop; T-Counter; 3 Screws to rezero; Capped Windage Turret
Sightron: S6 [= SVI] ED FFP •MIL MH-7 IR Ret. No. 66003 •MOA MOA-8 IR No. 66004	1650; 1700	Life		5-30x	22.7-3.8	56		Y	75	0.1mi 1/4mo	10 mi 25 mo	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid, CD	.03 ^{mi} .10 ^{mo}	34	33.3 944g	16.7" 42c	0-Stop; 3 Screws to rezero

				Magni. → FoV	→ Eye Box			Exposed Turrets				Holdoff Reticle				Dimensions				
in 2019, some 2020, 2021, 2022, 2023, 2024	Price: Low; Mfctr.'s in US \$	Warranty	Springer-Rated	Magnification	FoV = Field of View @ 100y (ft)	Obj. ∅ Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adj. (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick O/S Posts?	Enough Dots, No's, CD CenterDot	Line thickness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Brand: Series Part No.																				
Riton: 5 Conquer (or X5) •TPSR MIL Ret. •BAF MOA Ret.	700; 1003, 1400	Life	Yes	4-28x	30-4 ³	56	8-2.0	Y	95	0.1mi ¼mo	10 mi 25 mo	MIL = MOA =	=MIL =MOA	FFP ⁴⁰ Thick O/S Posts	D, N, Grid, CD	.035 ^{mi} .12 ^{mo} ?mi ?mo	34	36.8 1043g	14.9" 38c	Parallax c. 13y 0-Stop w/ 70moa Limit ⁴² ; 3 Screws to rezero
Vector: Taurus Gen. 2 ED <small>No. SCFF-33</small>	?; 537	Life, NoRec.		3-24x	41-5 ¹	56	19-2.3	Y	100	0.1 mil	10 mil	MIL =	=MIL	FFP ⁵³ Thick O/S Posts	D, N, Grid, CD	.03 ^{3mi} .11 ^{mo}	34	35.5 1007g	13.9" 35c	0-Stop
Vector: Continental 34mm • No. SCFF-29 VCT (typical grid) • No. SCFF-40 MBR (w/ 25mil elev. holds and person-ranging diagram) • No. SCFF-39 MBR FDE (same ret. as SCFF-40) Scope Color is FDE.	680; 850	Life, NoRec.		4-24x	30.6-5 ¹	56	8-2.3	Y	115	0.1 mil	10 mil	MIL =	=MIL	FFP ²⁵ Thick O/S Posts	D, N, Grid, CD	.04 ^{mi} .14 ^{mo}	34	27.5 780g	14.3" 36c	0-Stop with 70moa Limit Locking Turrets mech. T-Counter FDE Color = Flat Dark Earth
Element: Theos •APR-2D MRAD Ret.	1980 on sale; 2800	Life, NoRec.		6-36x	20 ³ -3.4	56	9-1.6	Y	100 40 Wind- age	0.1 mil	12 mil	MIL =	=MIL	FFP ⁵¹ Thick O/S Posts	D, N, Grid	??	34	36.5 1035g	14.8" 38c	0-Stop, mech. Turn Counter, Toolless Re-zero, Wind. Capped
Vortex: Razor HD Gen. II [no Gen. I or II] EBR-7D Ret.: •MIL Ret. No. RZR-63602 •MOA Ret. No. RZR-63601	3000; 4000	Life		6-36x	20 ⁵ -3.5	56	?	Y	125 55 Wind- age	0.1mi ¼mo	10 mi 25 mo	MIL = MOA =	=MIL =MOA	FFP ³⁷ Thick O/S Posts	D, N, Grid, CD	.03 ^{mi} .10 ^{mo}	34	31.8 1279g	15.3" 39c	0-Stop with 95moa Limit Locking Turrets mech. T-Counter
Bushnell: Match Pro ED	—; 700	Life NoRec.		5-30x	24.5-4 ¹	56	?	Y	103	0.1 mil	10 mil	MIL =	=MIL	FFP ³⁴ Thick O/S Posts	D, N, Grid, CD	.04 ^{mi} .14 ^{mo}	34	32.0 907g	15.4" 39c	Parallax 15y 0-Stop; Locking Turrets; Toolless Re-zero; mech. T-Counter
Vector: Continental 34mm X6 • No. SCFF-30 VCT • No. SCFF-41 MBR (w/ 25mil elev. holds and person-ranging diagram)	710; 900	Life, NoRec.		5-30x	24.7-4 ¹	56	8-1.8	Y	88 min had 96 moa	0.1 mil	10 mil	MIL =	=MIL	FFP ²⁶ Thick O/S Posts	D, N, Grid	.03 ^{mi} .10 ^{mo}	34	28.6 810g	15.4" 39c	0-Stop with 70moa Limit Locking Turrets mech. T-Counter
Riton: 7 Conquer (formerly X7) •ODEN Ret.	1000; 1800	Life	Yes	3-24x	35-4.6	56	6.6-2.2	Y	120	0.1 mil	10 mil	MIL =	=MIL	FFP ⁴⁸ Thick O/S Posts	D, N, Grid, CD	.05 ^{mi} .17 ^{mo}	34	35.0 992g	13.9" 35c	Parallax is c. 15y (≠ "20y") 0-Stop with 70moa Limit ⁴² ; 3 Screws to rezero
Element: Nexus Gen. 2 •APR-1C MRAD Ret. •APR-2D MRAD Ret. •APR-1C MOA Ret. •APR-2D MOA Ret.	2000; 2000	Life		4-25x	29 ² -4.7	50	7-2.0	Y	100 40 Wind- age	0.1mi ¼mo	10 mi 20 mo	MIL = MOA =	=MIL =MOA	FFP Thick O/S Posts	•D, N •+Grid •D, N •+Grid	?	30	30.7 870g	13.8" 35c	Toolless 0-Stop T Turn Counter Toolless Rezero Capped Windage Turret
Maven: RS.4 •CFR-MIL Ret. •SHR-MIL Ret. •MOA-2 Ret. [Not SHR-W Ret.]	1800; 1800	Life	?	5-30x	23 ³ -3.9	56	9-1.9	Y	120	0.1mi 0.1mi ¼mo	10 mi 10 mi 25 mo	MIL = MIL = MOA =	=MIL =MIL =MOA	FFP Thick O/S Posts	All: CD •D,N, Grid, •5mi Elev.,N •D,N, Grid	??	34	35.4 1004g	12.8" 33c	Parallax is <11y. 0-Stop; Toolless Re-zero; T Turn Counter
Apex: Rival	1600; 2000	Life NoRec.		4-32x	29.9-3.7	56	8-1.6	Y N3	110 70 Wind- age	0.1 mil	15 mil	MIL =	=MIL	FFP Thick O/S Posts	D, N, Grid, CD	.03 ^{mi} .10 ^{mo}	34	37.0 1049g	15.0" 38c	Parallax 15y True 0-Stop Locking Turrets mech. T-Counter 3 Screws to rezero

				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						
in 2019, some 2020, 2021, 2022, 2023, 2024	Price: Low; Mfctr.'s in US \$	War-ranty	Springer-Rated	Magni-fication	FoV = Field of View @ 100y (ft)	Obj. ∅ Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adjmt (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick O/S Posts? FFP — SFP Calibration at ?	Enough Dots, No's, CD CenterDot Grid	Line thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Brand: Series Part No.																				
Riton: 7 Conquer (formerly X7) •PSR MIL Ret.	700, 1000, 1310; 1683, 2300	Life	Yes	4-32x	27° ⁰ -3° ⁴	56	7-1.6	Y	105	0.1 mil	10 mil	MIL =	=MIL	FFP ⁴¹ Thick O/S Posts	D, N, Grid, CD	??	34	37.0 1049g	15.0" 38c	Parallax is <11y. 0-Stop w/ 70moa limit ^{N2} ; 3 Screws to rezero
Nightforce: NX8 •MOAR F1 Ret. •MIL-C F1 Ret. •MIL-XT Ret.	2150; 2150	Life, Anyb., Register		4-32x	26° ¹ -4.6	50	7-1.6	Y	90 ⁷⁰ Windage	1/4mo — 0.1mi	25 mo — 10 mi	MOA = — MIL =	=MOA — =MIL	FFP ⁴⁵ Thick O/S Posts	•D, N — •D, N, CD • and Grid	?? ^{mi} ?? ^{mo} .04 ^{mi} .14 ^{mo} ?? ^{mi} ?? ^{mo}	30	28.6 811g	13.4" 34c	0-Stop; 3 Screws to rezero; Locking Turrets
Sightron: [S8=] SVIII FFP ED •LRM Ret. No. 29001 •MH-6 Ret. No. 29000	2900; 2000 on sale, 2900	Life		5-40 x	23.7° ⁰ -3° ⁰	56	very small	Y	135 ⁷⁰ Windage	0.1 mil	10 mil	MIL =	=MIL	FFP ⁵⁰ Thick O/S Posts	•D, N, CD •+Grid	.03 ^{mi} .10 ^{mo}	40	49.0 1389g	16.8" 43c	0-Stop; T-Counter; 3 Screws to rezero; Locking Turrets; sold with low rings
in 2019, some 2020, 2021	Price: Low ; Mfctr.'s US \$	War-ranty	Springer-Rated	Magni-fication	FoV = Field of View @ 100y (ft)	Obj. ∅ Dia (mm)	Exit Pupil (mm)	IR Y, N	Max. Elev. Adjmt (MOA)	1 Click =	1 T. Turn =	Turrets in:	Reticle in:	Thick O/S Posts? FFP — SFP Calibrated at ?	Enough Dots, No's, CD CenterDot Grid	Line Thick-ness	Tube Dia-meter	Weight (oz) (g)	Length (inch) (cm)	Misc. + Reviewers' "Comments"
Brand: Series Part No.																				
				Magni. → FoV	→ Eye Box	Exposed Turrets				Holdoff Reticle				Dimensions						

Notes About Different Scopes – N1, N2, N3, etc.:

N1: Sightron ExacTrack turret adjustment system: Though the turrets of the indicated scope are capped, they are made for dialing, because they use the same ExacTrack turret adjustment system as the uncapped scopes of the following series (as of the 2012 and 2022 catalog): S-TAC | SVIII | S6 | SV | SIII | SII | SII Big Sky

→ Dialing Turrets (capped w/ ^{N1})

N2: This has been confirmed by various shooters on Snipers Hide. Riton, upon insistant request sent them a turret without 0-stop in order to be able to use the full elevation adjustment. It seems that a bit of grinding can achieve the same without asking Riton.

<https://www.snipershide.com/shooting/threads/riton-x7-question.7169618/#post-10871354>

N3: Not daylight bright.

Review EPIK ARMS, @ 10:42min: <https://www.youtube.com/watch?v=JhR4kNjZJXg>

N4: This scope has "Gen. 2" in its name, as it belongs to the second generation of its series – but is *not the second iteration of this particular scope* with this particular magnification range and objective diameter.

Reticles: Footnotes: Links for Views or Videos of FFP Reticles at Different Magnifications

Note on more detailed reticle diagrams:

- Athlon: Each scope on their homepage includes detailed diagrams: <https://athlonoptics.com>
- Discovery: many scopes reticles are listed here: <https://discoveryoptics.co.uk/reticles/>

¹ Discovery: HD/34mm: 4-24x50 FFP: Reticle at all magnifications: @ 4:56min:

<https://www.youtube.com/watch?v=DerSb0Y-d34>

² Vector: Taurus: 5-30x56 FFP: Reticle at all magnifications: @ 10:04min:

<https://www.youtube.com/watch?v=xV6m6OUR33c>

Reticle at all magnifications, in front of a favorable background:

<https://www.youtube.com/watch?v=pQ82hBoSwdw>

³ Discovery: HD/34mm: 5-30x56 FFP:

Reticle at all magnifications, in front of a non-favorable background: @ 1:51min:

<https://www.youtube.com/watch?v=b4EF9OMRv2M>

Reticle at all magnifications: @ 29.55min:

<https://www.youtube.com/watch?v=PQSVqejaEKE>

Illuminated Reticle at all magnifications, but no *non-illuminated* view: @ 1:23min:

<https://www.youtube.com/watch?v=31y22fzGb1M>

⁴ Discovery: HD: 5-25x50 FFP: *Illuminated* Reticle at all magnifications, but no *non-illuminated* view: @ 4:29

<https://www.youtube.com/watch?v=SJZNGszt0E4>

non-illuminated view: @ 2.35min:

<https://www.youtube.com/watch?v=zR9mUevdVX0>

⁵ Athlon: Midas TAC: Reticle at min. and max. magnification:

- MIL: APRS2 Reticle: <https://athlonoptics.com/product/midas-tac-6-24x50-aprs2-ffp-mil-scope/>

- MIL Grid: APRS3 Reticle: <https://athlonoptics.com/product/midas-tac-6-24x50-aprs3-ffp-mil-scope/>

- MOA: APLR4 Reticle: <https://athlonoptics.com/product/midas-tac-6-24x50-aplr4-ffp-moa-scope/>

⁶ Athlon: Helos BTR: Reticle at min. and max. magnification:

- APMR MIL Grid: <https://athlonoptics.com/product/rifle-scopes-helos-btr/>

- APLR2 MOA: <https://athlonoptics.com/product/rifle-scopes-helos-btr-3/>

⁷ Discovery: ED: 6-24x50 FFP: Reticle at all magnifications: @ 6.44min:

<https://www.youtube.com/watch?v=1Ph66qud50M>

⁸ Vortex: Diamondback: 6-24x50 FFP: Reticle at all magnifications: @ 6.55min:

<https://www.youtube.com/watch?v=weHwC3amwfE>

⁹ Blackhound: Genesis: 6-24x50 FFP: Reticle at min. and max. magnification:

- Alpha MIL reticle: Owner's Manual: <https://www.blackhoundoptics.com/product/genesis-6-24x50-ffp-mil/>

- Ascent MOA reticle: <https://www.blackhoundoptics.com/product/genesis-6-24x50-ffp-moa/>

¹⁰ Hawke: Sidewinder: 30 SF FFP: 6-24x56 [No. 17420]: Reticle at min. and max. magnification:

<https://us.hawkeoptics.com/sidewinder-30-sf-ffp-riflescopes.html>

¹¹ Falcon: S18i 3-18x50 FFP: Reticle at all magnifications: @ 2:06min:

<https://www.youtube.com/watch?v=RGmnOFp2fUU>

¹² Falcon: F30 6-24x50 FFP: Reticle at 6x magnification (24x at the mfctr's webpage): @ 5:33min:

<https://www.youtube.com/watch?v=swZJkEM76hw>

¹³ Athlon: Argos BTR Gen. 1: 6-24x50 FFP: Reticle at min. and max. magnifications:

- APMR MIL reticle: <https://athlonoptics.com/product/rifle-scope-argos-6-24x50/>

- APLR2 MOA reticle: <https://athlonoptics.com/product/rifle-scopes-argos-6-24x50-atmr-ffp-ir-moa/>

¹⁴ Hawke: Frontier 30 FFP: 5-25x56, Mil Pro 25x Reticle [No. 18540]: Reticle at 25x magnification: @ 5:25min

<https://www.youtube.com/watch?v=Gcud4IGjOA>

Cf. also footnote ³⁶ for the same reticle in an FFP scope, and both reticles have to cover a 5-fold magnification range and thus will be similar at the bottom end of the magnification and the top end.

¹⁵ Vector: Counterpunch: 6-25x56 FFP: Reticle at all magnifications:

<https://www.youtube.com/watch?v=E9qIPzpxvTQ>

¹⁶ Vector: Marksman: 6-24x50 FFP: Reticle at all magnifications: @ 6:33min:

<https://www.youtube.com/watch?v=BnLJLvXVSol>

and @ 4.47min: <https://www.youtube.com/watch?v=nepYkyfjpng>

¹⁷ Vector: Tourex: 6-24x50 FFP: Reticle at various magnifications: @ 2.04min:

https://www.youtube.com/watch?v=zD-HN8uU_fo

¹⁸ MTC: King Cobra F1: 6-24x50 FFP: Reticle at all magnifications: @ 1:03min:

<https://www.youtube.com/watch?v=4RjMgVRqTM4>

¹⁹ Aztec: Emerald: 5.5-25x50 FFP: Reticle at all magnifications: @ 4.21min:

<https://www.youtube.com/watch?v=8GwntsJAuTU>

²⁰ ACME Machine: 6-24x50 FFP: Reticle at 6x, 14x, and 24x magnifications: @ 1:55min:

<https://www.youtube.com/watch?v=LCI2SM7G2t0>

Reticle at 6x and 24x, MOA:

<https://www.acmemachine.com/optics-sights/6-24x50mm-first-focal-plane-tactical-rifle-scope-tr-mil-reticle/?variant=48625453254>

²¹ Optisan: EVX: 6-24x50 FFP F1: Reticle at 6x, 15x, and 24x magnifications: @ 12:33min:

<https://www.youtube.com/watch?v=RuXmjOLxwNw>

²² Swampfox: Kentucky Long: 5-30x56 FFP: MOA Reticle: Reticle at all magnification: @ 3:16min:

<https://www.youtube.com/watch?v=riYsEFSXYyw>

²³ Vector: Taurus: 4-24x50 FFP: Reticle at min. and max. magnification: @ 0:37min (play at slowest playback speed,

the min. magnification will be shown only for a *split second* – but shows how thin the outside post really are, they are not really “medium”:

<https://www.youtube.com/watch?v=rZRVuR5-398>

- ²⁴ Discovery: HD: 4-20x50 SFIR FFP: Reticle at all magnifications: @ 2:42min:

https://www.youtube.com/watch?v=C1qBt7yg_ek

- ²⁵ Vector: Continental 34mm: 4-24x56 FFP: Reticle at all magnifications: @ 1:27min:

<https://www.youtube.com/watch?v=ceLSb2gkmbk>

<https://www.vectoroptics.com/data/uploads/2020/06/22/1592831142.jpg>

- ²⁶ Vector: Continental 34mm: 5-30x56 FFP: Reticle at all magnifications: @ 2:23min:

<https://www.youtube.com/watch?v=S97yza3Fph4>

Reticle at min. and max. magnification:

<https://www.vectoroptics.com/data/uploads/2020/06/22/1592831200.jpg>

- ²⁷ Nikko: Diamond FFP 30: 6-24x50: *Skeleton HMD Reticle* (No. NSFFP62450HMD) (the PRR Reticle is different and does have thick outside posts!): Reticle at different magnifications: 6x: @ 13:44min | 16x: @ 14:14min | 24x: 14:31min:

https://www.youtube.com/watch?v=VOy2IWN7N_c

- ²⁸ Nikko: Diamond FFP: Nikko's *Skeleton HMD* reticle is used in several scopes and it does not have thick outside posts; the double lines used are just as thin as the rest of the reticle. Here is an example of the *Skeleton HMD* reticle, in the Diamond FFP 30mm 6-24x50: Reticle at different magnifications: 6x: @ 13:44min | 16x: @ 14:14min | 24x: 14:31min:

https://www.youtube.com/watch?v=VOy2IWN7N_c

- ²⁹ Element: Titan: 5-25x56:

MIL Ret. APR-1C: Likely from 5x–25x – recommended to play it with slow motion: @ 3:46min

<https://www.youtube.com/watch?v=eSGzTPkRxZY>

MIL Ret. APR-1C + APR-1D: @ 5:02min:

<https://www.youtube.com/watch?v=2CmHU4lhqQ>

MIL Ret. APR-1D: @ 6:50min:

<https://www.youtube.com/watch?v=0-C6DhTkDgw>

MOA Ret. EHR-1C + EHR-1D: @ 6:31min:

<https://www.youtube.com/watch?v=2CmHU4lhqQ>

Manual of all four reticles, at 5x and 25x:

<https://element-optics.com/wp-content/uploads/2020/10/5x7-TITAN-MANUAL-Amended.pdf>

Difference between Titan and Nexus (more expensive – because of lighter and smaller, with higher quality)

<https://www.youtube.com/watch?v=W4qdh7-v2mM>

- ³⁰ Element: Helix: 6-24x50 FFP:

APR-2D MRAD: 6x and 24x: @ 1:01min and 1:16:

<https://www.youtube.com/watch?v=DggOXpR2ymY>

APR-2D MOA: Reticle at all magnifications: @ 0:14min

<https://www.youtube.com/watch?v=YeWbkurVV0o>

- ³¹ Athlon: Argos BTR Gen. 2: 6-24x50 FFP: Reticle at min. and max. magnifications:

• APMR MIL reticle: <https://athlonoptics.com/product/argos-btr-gen2-6-24x50-apmr-ffp-ir-mil-copy/>

• APLR2 MOA reticle: <https://athlonoptics.com/product/argos-btr-gen2-6-24x50-atmr-ffp-ir-moa-copy/>

- ³² Hi-Lux: PentaLux: TAC-VF 4-20x50 FFP G2: 20x: @ 0:20min:

https://www.youtube.com/watch?v=NAbX_POUKgc

@ 5:12min:

<https://www.youtube.com/watch?v=dvzUNANmNXs>

- ³³ Swampfox: Kentucky Long: 4-24x50 FFP:

Cf. the other models of this series that have the same six-fold magnification range, resulting in the same ratio of reticle increase/decrease:

Kentucky Long: 5-30x56 FFP: MOA Reticle: Reticle at all magnification: @ 3:16min:

<https://www.youtube.com/watch?v=riYsEFSXYyw>

And also: Swampfox: Kentucky Long: 2-12x44 FFP: MOA: Reticle at 2x and at 12x(?):

<https://images-na.ssl-images-amazon.com/images/I/71%2B5YMUAXfL.AC.SL1500.jpg>

<https://images-na.ssl-images-amazon.com/images/I/71aX%2BZ5aDFL.AC.SL1500.jpg>

- ³⁴ Swampfox: Warhawk: 5-25x56 FFP: MOA Reticle: at 5x: @ 1:04min (very briefly, use slo-mo, or pause it):

<https://www.youtube.com/watch?v=fFh5jleVgxE>

Cf. also the same reticle in the Kentucky Long models (several videos available; however the Warhawk has only a five-fold magnification range, as opposed to the Kentucky Long's six-fold, which means the reticle will increase/decrease 17% less).

³⁵ Shepherd: BRS: 5-25x56 FFP: Reticle at min. and max. magnifications:

BRS-MIL Ret.: <https://shepherdscopes.com/wp-content/uploads/2020/06/BRS-MIL-5-25x.jpg>

Also: <https://shepherdscopes.com/wp-content/uploads/2021/03/BRS-5-25-Instructions.pdf>

BRS-MOA Ret.: [not found yet]

³⁶ Hawke: Frontier 30 FFP: 4-20x50, Mil Pro 20x Reticle [No. 18530]: at 4x to 20x: @ 7:55min | And illuminated at night and during daylight: @ 9:09min:

<https://www.youtube.com/watch?v=E9SLP7RiaWg>

³⁷ Vortex: Razor HD Gen. II: 6-35x56, EBR-7D Mil Reticle: Reticle at all magnifications: @ 21:39min, and throughout the video, including illumination, and including comparisons to other scopes:

https://www.youtube.com/watch?v=h_KRIbzOMKU

³⁸ Hawke: Frontier 34 FFP: 5-30x56, Mil Pro Ext. Reticle [No. 18640]:

Cf. another model of this series that has the same six-fold magnification range, resulting in the same ratio of reticle increase/decrease:

Hawke: Frontier 34 FFP: 3-18x50, Mil Pro Ext. Reticle [No. 18620]: Reticle at all magnifications, illuminated: @ 2:02min:

<https://www.youtube.com/watch?v=3ztkmBiv4lk>

³⁹ Riton: 5 Conquer: 5-25x50 FFP, MIL: Reticle at all magnifications: @ 8:52min and more at 12:39min:

<https://www.youtube.com/watch?v=kWvTDIOmMoc>

Reticle subtensions: MIL: <https://www.amazon.com/Riton-Optics-Conquer-5-25x50-MRAD/dp/B082DNFXKB>

Reticle subtensions: MOA: <https://www.amazon.com/Riton-Optics-Conquer-5-25x50-MOA/dp/B082DNVW2S>

⁴⁰ Riton: 5 Conquer: 4-28x56 FFP:

Reticle subtensions: MIL: Page 7: <https://ritonoptics.com/wp-content/uploads/2022/04/5-Conquer-4-28x56-Manual-2022.pdf>

Reticle subtensions: MOA: ?

⁴¹ Riton: 7 Conquer: 4-32x56 FFP, MIL:

Reticle subtensions: <https://ritonoptics.com/wp-content/uploads/2019/12/7Conquer4-32x56.RitonOptics.ReticleSubtensions.jpg>

or: <https://ritonoptics.com/wp-content/uploads/2022/04/7-Conquer-4-32x56-Manual-2022.pdf>

Reticle at all magnifications, with and without illumination: <https://www.youtube.com/watch?v=tpG7mCpb0v8>

Reticle thickness: The manual and the webpage do not give the thickness of the most basic reticle line, only subtensions and others. I had published in an earlier version of this Scope Specs Table a thickness of 0.02mil. This is wrong. The manual, when enlarged, shows this is the length of a short but both-sided hashline.

<https://ritonoptics.com/wp-content/uploads/2022/04/7-Conquer-4-32x56-Manual-2022.pdf>

Also, the video of the reticles does *not* give the impression that the reticle lines are 3 or 4 times thicker than most other scopes: <https://www.youtube.com/watch?v=tpG7mCpb0v8>

⁴² Arken: EPL4: 6-24x50 FFP:

MIL VHR Subtensions:

https://www.arkenopticsusa.com/ipx/w_1920,q_100/https%3A%2F%2Fcdn.sanity.io%2Fimages%2Fu57cw5zd%2Fproduction%2Fdaa6661e721237bec2a01cfd12962abab2540216-4005x4005.png%3Fauto%3Dformat?url=https%3A%2F%2Fcdn.sanity.io%2Fimages%2Fu57cw5zd%2Fproduction%2Fdaa6661e721237bec2a01cfd12962abab2540216-4005x4005.png%3Fauto%3Dformat&w=1920&q=100

MOA VHR Subtensions:

https://www.arkenopticsusa.com/ipx/w_1920,q_100/https%3A%2F%2Fcdn.sanity.io%2Fimages%2Fu57cw5zd%2Fproduction%2F3917883977bc6e2f37f55eab92830f303f99d20d-4005x4005.png%3Fauto%3Dformat?url=https%3A%2F%2Fcdn.sanity.io%2Fimages%2Fu57cw5zd%2Fproduction%2F3917883977bc6e2f37f55eab92830f303f99d20d-4005x4005.png%3Fauto%3Dformat&w=1920&q=100

⁴³ Bushnell: Match Pro ED: 5-30x56 FFP MIL:

Subtensions: https://www.bushnell.com/on/demandware.static/-/Library-Sites-HuntShootAccessoriesSharedLibrary/default/dw8dd6d632/productPdfFiles/MP53056DM-DMI_MatchPro_Manual_5LIM_1022_w

- ⁴⁴ Bushnell: Match Pro: 6-24x50 FFP MIL: Reticle at all magnifications, illuminated:
@ 9:43min: https://youtu.be/XT8v6Uwr_FQ?t=583
also: @ 13:47min: https://youtu.be/XT8v6Uwr_FQ?t=827
- ⁴⁵ Nightforce: NX8: 4-32x50 F1
MIL-C:
Note: The MIL-C reticle is sometimes wrongly depicted in seller webpages as not having thick outside posts.
Reticle at all magnifications: <https://www.youtube.com/watch?v=Sz2n06itBy4>
and also: @ 0:06min: <https://www.youtube.com/watch?v=nu2IE5DBJzo>
- MIL-XT:
Important Note: The camera in this video was incorrectly set to automatic exposure. Therefore, the camera when filming a largely dark image (woods) increased the brightness of the image automatically. This caused the reticle lines *to be washed out* when they are in front of a light colored background (white target). When the scope magnification was increased, the image was less of the dark woods and more of the white target, which caused the camera to adjust the brightness again – this time appropriate to the white target at lower brightness. This can be observed when at 0:13min the reticle lines suddenly are not washed out anymore but become visible very nicely.
Reticle at all magnifications: @ 0:07min: <https://www.youtube.com/watch?v=0P2F3lfapRc>
- MOAR F1:
Not found yet.
Subtensions: Note: The reticle subtensions on the Nightforce webpage are probably incorrect because the reticle manual they offer (as of Jan. 2, 2023) gives the subtension measurements only for scopes other than the NX8 4-32x50 F1.
- ⁴⁶ Falcon: Endura: 3.5-25x56 FFP
MIL: Diagram: <https://www.falconoptics.com/wp-content/uploads/2022/06/B28-Grid-Dot-B2GD-FFP.pdf>
MOA: Reticle at all magnifications: @ 11:30min: <https://youtu.be/MwpYgGiaSDI?t=691>
- ⁴⁷ Discoveryopt: ED-ELR: 5-40x56 SFIR FFP: at 5x, 15x, and 40x:
http://www.discoveryopt.com/repository/image/3508bf75-9d1f-46a0-9fb0-503e708b2476.jpg_%7Bi%7Dxaf.jpg
- ⁴⁸ Riton: 7 Conquer: 3-24x56 FFP: Reticle at all magnifications: @ 3:13min:
<https://www.youtube.com/watch?v=LZAgWSQJzt0>
- ⁴⁹ Apex: Rival: 4-32x56 FFP: Reticle at all magnifications: @ 1:58min:
<https://www.youtube.com/watch?v=3pPJKCqVmXE>
- ⁵⁰ Sightron: [S8=] SVIII: 4-40x56 FFP: no images found yet beyond the manufacturer's, here:
<https://sightron.com/collections/sviii-series>
However, a shooter on Snipers Hide has described the visibility of different reticle details at varying magnifications, here:
<https://www.snipershide.com/shooting/threads/magnification-whores-check-this-out.7086276/#post-9748119>
- ⁵¹ Element: Theos: 6-36x56 FFP: Reticle at all magnifications: @ 2:26min:
https://www.youtube.com/watch?v=WgO4wU8_7Es
- ⁵² Falcon: Endura S40i: 5-40x56i ED FFP: Reticle at 5x and 40x:
<http://www.falconoptics.com/wp-content/uploads/2024/02/B9GDi-Diagram-with-40x-Email-Revised.jpg>
- ⁵³ Vector: Taurus Gen. 2: 3-24x56 ED FFP: Reticle at 3x and 24x:
<https://www.vectoroptics.com/products/view/id/SCFF-33.html>
- ⁵⁴ Sun Optics: FFP Variable No. CS41-62450: 6-24x50 FFP: Reticle measurements:
<https://op1.0ps.us/978-550-fffff-no-upscale/opplanet-sun-optics-tactical-hunter-glass-etched-reticle@2x.webp>

Important Scope Tests and Reviews

- 4x min. to 36x max. Outdoor Life (2023). 'The Best Long Range Rifle Scopes of 2023'
<https://www.outdoorlife.com/gear/best-long-range-rifle-scopes/>